| MODELS. | | | | | | | |
|---------|---|---------------------------------|-----|-----|--------|-----------|--|
| | | | | | | | |
| 1 | Microprocessor based 2 Zone Conventional Fire Alarm Control panel 2 hours battery back up with built in battery charger. | Local/Imported | 1 | No | 10,000 | 10,000 | |
| 2 | Optical type, LED, self diagnostic conventional smoke detector with base | System sensor/2351E+ B401 | 14 | No | 1,150 | 16,100 | |
| 3 | Rate of rise cum fixed temperature type Conventional heat detector with base . | System sensor/5351E+ B401 | 1 | No | 1,100 | 1,100 | |
| 4 | Glass break type Manual Call point with chrome plated hammer and chain | Local | 2 | No | 650 | 1,300 | |
| 5 | Electronic Hooter for alarm/evacuation signal. | Local | 2 | No | 700 | 1,400 | |
| 6 | Two Core X 1.5 sqmm Copper Armored cable (ISI mark.) | | 125 | Mtr | 80 | 10,000 | |
| | TOTAL of A | | | | | 39,900.00 | |

Area Assumed 5000 Sq Ft SAMPLE QUOTE : PRICES ARE NOT REALISTIC AND VARIES WITH ORDER QUANTITY, MAKE AND

| В | CCTV SYSTEM | | | | | | |
|-------|---|----------|-----|------|-----------|-------|--|
| Sr.No | DESCRIPTION | MODEL NO | QTY | UNIT | UNIT RATE | TOTAL | |
| 1 | High Resolution 4 Channel MPEG -4 Digital Video Recorder (DVR) with 240 GB internal harddisk for recording. | AVC783 | 1 | Nos | 19,000 | 19000 | |
| | 1/3" Color Super CCD Image sensor, 3.6 mm lens, 480 TV Lines | AVC508 | 4 | Nos | 3,500 | 14000 | |
| | NOTE: Cameras are considered according to our assumption | | | | | | |
| 3 | Power Supply for cameras. | Local | 4 | Nos | 550 | 2200 | |
| 4 | High Resolution 14" CCTV Colour Monitor | Zicom | 1 | Nos | 12,500 | 12500 | |
| 5 | RG6 Cable in 25 mm PVC medium conduit with saddles & spacers suitably mounted on wall/ceiling for looping of each camera to DVR independently. | | 100 | Mtr | 80 | 8000 | |
| 6 | Two core X 1.5 sqmm flexible cable in 25 mm PVC medium conduit with saddles & spacers suitably mounted on wall/ceiling for supply of power to cameras. | | 100 | Mtr | 65 | 6500 | |
| | TOTAL of B | | | | | 62200 | |

| С | ACCESS CONTROL SYSTEMS | | | | | | |
|-------|---|----------|-----|------|-----------|-----------|--|
| Sr.No | DESCRIPTION | MODEL NO | QTY | UNIT | UNIT RATE | TOTAL | |
| 1 | Main Access Controller with power supply | SY210NT2 | 1 | Nos | 15,000.00 | 15,000.00 | |
| 2 | Contactless Proximity Card Reader(125KHz) White in color | SYRDS1 | 1 | Nos | 3,500.00 | 3,500.00 | |
| 3 | Access control cards with Printing Photo ID & Lanyards. | | 60 | Nos | 150 | 9,000 | |
| | Note: We have assumed 60 numbers of employees and one access door. | | | | | | |
| 4 | Electromagnetic Door Lock | Local | 1 | Nos | 2,000 | 2,000 | |
| 5 | Access control managment system software | SY-TAMS | 1 | Nos | 7,500 | 7,500 | |
| 6 | RS485 Convertor(PC link) for Controller to PC communication | sylink | 1 | Nos | 10,000 | 10,000 | |
| 7 | Push Button for exit | Local | 1 | Nos | 750 | 750 | |
| 8 | Eight core X 1 sqmm sheilded cable with 25 mm PVC conduits For connection of Reader with Controller independently | | 40 | Mtr | 90 | 3,600 | |
| 9 | Four core X 1 sqmm sheilded cable with 25 mm PVC conduits for connection of Magnetic lock & push button to controller | | 60 | Mtr | 75 | 4,500 | |
| | TOTAL of C | | | | | 55,850.00 | |

| D | PUBLIC ADDRESS SYSTEM | | | | | |
|-------|---|----------|-----|------|-----------|--------|
| Sr.No | DESCRIPTION | MODEL NO | QTY | UNIT | UNIT RATE | TOTAL |
| 1 | 6" ceiling recessed surface mounted sound speaker with line matching transformer. | RNS6/T | 15 | Nos | 800 | 12,000 |
| 2 | 120 W 24V dc,50 Hz to 18 kHz mixing amplifier with microphone input. | LBD1912 | 1 | Nos | 11,000 | 11,000 |
| 3 | 6Watt Volume Control | Local | 2 | Nos | 750 | 1,500 |
| 4 | Single CD Player for music source | | 1 | Nos | 5,500 | 5,500 |
| 5 | Table -Top Microphone with mounting stand. | LBB1950 | 1 | Nos | 4,800 | 4,800 |
| 6 | Two core X 1.5 sqmm flexible copper audio Cable in 25 mm PVC medium conduit suitable for PA System. | | 100 | Mtr | 80 | 8,000 |
| 7 | Six core X 1.5 sqmm flexible copper audio Cable in 25mm PVC medium conduit suitable for volume control. | | 20 | Mtr | 90 | 1,800 |
| | TOTAL of D | | | | | 44,600 |

NOTE :Cable quantity required in all above systems may change as per area

| Е | FIRE EXTINGUISHERS | | | | | |
|-------|--|----------|-----|------|-----------|------------|
| Sr.No | DESCRIPTION | CAPACITY | QTY | UNIT | UNIT RATE | TOTAL |
| | | | | | | |
| 1 | ABC Type Fire Extinguisher (ISI Mark) | 5Kg | 1 | No | 3,500 | 3,500 |
| 2 | ABC Type Fire Extinguisher (ISI Mark) | 2kg | 2 | Nos | 2,500 | 5,000 |
| 3 | CO2 Type Fire Extinguisher (ISI Mark) | 2Kg | 1 | No | 5,600 | 5,600 |
| | NOTE : CO2 Type Extinguisher is used for server room or BMS room. | | | | | |
| | TOTAL of E | | | | | 14,100.00 |
| | | | | | | |
| | | | | | | |
| | GRAND TOTAL(A+B+C+D+E) | | | | | 216,650.00 |

email us : info@vedantsystems.com,





joint venture

3 Jacqueline Apts. Near holy Cross School,K-Villa Rd,Thane(W)-400 601 Tel:022 25473010/11